

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
6 October 2005 (06.10.2005)

PCT

(10) International Publication Number  
**WO 2005/093228 A1**

(51) International Patent Classification<sup>7</sup>: **F01N 1/08**, 1/12

(21) International Application Number:  
PCT/IB2005/000731

(22) International Filing Date: 21 March 2005 (21.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
TO2004U000041 26 March 2004 (26.03.2004) IT

(71) Applicant (for all designated States except US): **SUPER-SPRINT S.r.l.** [IT/IT]; Via Pisa 24, I-46100 Mantova (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GILLI, Alessandro** [IT/IT]; Piazza 80a Fanteria, I-46100 Mantova (IT).

(74) Agents: **SPANDONARI, Carlo** et al.; Spandonari & Modiano s.r.l., Corso Duca degli Abruzzi, 16, I-10129 Torino (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MUFFLER FOR EXHAUST SYSTEMS OF VEHICLES



(57) Abstract: The muffler comprises a tubular shell (12) which is internally lined with a noisedeadening material and is closed at its ends by a front wall (14) provided with an inlet (16) connectable to receive exhaust gas, and by a rear wall (19). A first chamber (26) and a second chamber (28), which are separated by a transverse wall (30) having an inlet opening (32) and an outlet opening (34), are defined within the tubular shell (12). A perforated inlet pipe (36) extends within first chamber (26) from the inlet (16) to the inlet opening (32). Gas-piping means (40, 42) extend within the first chamber (26) and have one end open to said outlet opening (34), and another end connectable to the exhaust pipes (44, 46, 50). The inlet opening (32) and the outlet opening (34) are substantially equal in diameter to the inlet pipe (36), and are interconnected via a toroidal duct (38) that is arranged within the second chamber (28) and is substantially equal in diameter to the inlet pipe (36).

WO 2005/093228 A1